

BPM131S Universal 130 Watt Series

- 100-240 Vac Universal Input
- Meets "ENERGY STAR" Program Requirements
- Single Output to 130W
- Regulated Output with Low Ripple
- Meets Safety Agency Requirements
- Impact Resistant Polycarbonate Enclosure
- Modified and Custom Designs Also Available
- Desktop Style




Model	Output Voltage DC (V)	Maximum Current (A)	Maximum Watts (W)	Ripple & Noise V _{p-p} max. (mV)
BPM131-S-12-X-XX	12	10.80	129.6	120
BPM131-S-15-X-XX	15	8.67	130.1	150
BPM131-S-18-X-XX	18	7.20	129.6	180
BPM131-S-24-X-XX	24	5.40	129.6	240

Input Specification	
Input Voltage Range	100 to 240VAC -10%, +10%
Line Frequency	47 to 63 Hz
Input Current	3.0A max. at 90VAC Input
Protection	Internal Primary Current Fuse, Inrush Limiting

Output Specification	
Line & Load Regulation (at End of Cable)	Line Regulation +/- 1%
	Load Regulation +/- 5%
Ripple & Noise	1% V _{p-p} max.
Transient Response	0.5ms for 50% Load change Typ.
Protection	Over-current Protection (Hiccup) Short Circuit Protection

Environmental Specification	
Operating Temperature	0°C to 40°C with no derating
Relative Humidity	5% to 95% non-condensing
Altitude	0 - 10,000 feet
Cooling	Convectional - Non vented case

Input Configuration	
	
IEC320	
C14 (F)	

Specify the input configuration Code in your Order.

General Specification	
Topology	Switching - Half bridge
Leakage Current	Less than 100uA
Dielectric Withstand	5,656VDC Primary - Secondary 2,150VDC Primary - F.G 500VDC Secondary - F.G
Storage Temperature	-30 °C to 85 °C
Efficiency	Minimum Average Efficiency in Active Mode ≥87%
Hold-up Time	18ms min. @115VAC
EMI	Complies with EMC Directives
Max. Power in No-Load	≤ 0.5W
MTBF	100,000 Calculated Hours Minimum.
Approvals and	UL60601-1, IEC/EN60601-1, K60950-1
Safety Standards	EMC : EN60601-1-1-2 / EN55011
Case and Dimension	8.2(L) x 2.5(W) x 1.6(H) [in] 209.4(L) x 64.4(W) x 41.5(H) [mm]
Case Material	Black 94V0 Polycarbonate
Cord and Connectors	16 AWG or 18 AWG 1,500mm 4 Conductor. Other cable and connectors are available.

Part Number Key				
BPM131	S	12	X	XX
Product Family Name	Single Output	Volt (DC)	Input Configuration	Customer Number

