

BPM350S Universal 350 Watt Series

- 100-240 Vac Universal Input
- Single Output to 350W
- Regulated Output with Low Ripple
- Meets Safety Agency Requirements
- Impact Resistant Polycarbonate Enclosure
- Modified and Custom Designs Also Available
- Desktop Style




Model	Output Voltage DC (V)	Maximum Current (A)	Maximum Watts (W)	Ripple V _{p-p} max. (mV)
BPM350-S-12-X-XX	12	25.00	300.0	120
BPM350-S-15-X-XX	15	20.00	300.0	150
BPM350-S-18-X-XX	18	19.40	349.2	180
BPM350-S-24-X-XX	24	14.58	349.9	240

Input Specification	
Input Voltage Range	100 to 240VAC -10%, +10%
Line Frequency	47 to 63 Hz
Input Current	5.0A max. at 90VAC Input
Protection	Internal Primary Current Fuse, Inrush Limiting

Output Specification	
Line & Load Regulation (at End of Cable)	Line Voltage +/- 1%
	Load Voltage +/- 5%
Ripple	1% V _{p-p} max.
Transient Response	0.5ms for 50% Load change Typ.
Protection	Over-current Protection (Hiccup) Short Circuit Protection

Environmental Specification	
Operating Temperature	0°C to 40°C with no derating
Relative Humidity	5% to 95% non-condensing
Altitude	0 - 10,000 feet
Cooling	Convectional - Non vented case

Input Configuration
 IEC320 C14 (F)
Specify the input configuration Code in your Order.

General Specification	
Topology	Switching - Half bridge
Leakage Current	Less than 100uA
Dielectric Withstand	5,656VDC Primary - Secondary
	2,150VDC Primary - F.G
	500VDC Secondary - F.G
Storage Temperature	-30 °C to 85 °C
Efficiency	≥85%
Hold-up Time	18ms min. @115VAC
EMI	Complies with EMC Directives
MTBF	100,000 Calculated Hours Minimum.
Approvals and Safety Standards	UL60601-1, IEC/EN60601-1, K60950-1 EMC : EN60601-1-1-2 / EN55011
Case and Dimension	12.06(L) x 5.23(W) x 2.47(H) [in] 306.5(L) x 133(W) x 62.8(H) [mm]
Case Material	Black 94V0 Polycarbonate
Cord and Connectors	16 AWG 1,500mm 6 Conductor. Other cable and connectors are available.

Part Number Key				
<u>BPM350</u>	<u>S</u>	<u>12</u>	<u>X</u>	<u>XX</u>
Product Family Name	Single Output	Volt (DC)	Input Configuration	Customer Number